FFU Cleanroom Technology

FANCommander 200 (ECE 03-0200-5E-MG)



The Advantages

- · Control and monitor up to 200 filter fan units
- Simple and clear, bilingual menus (German/English)
 - Full graphic display with lighting
 - Suitable for mounting on a wall or installing in a control cabinet IP65 wall-mounted unit/IP20 cabinet installation unit with the same functionality

Hardware

- 24V=/100mA
- Modern operating concept with rotary pushbutton
- Realtime clock
- GBUS or Modbus 2 separate lines (freely configurable)
- 3 digital inputs (1 x day/night switch, 2 x release controllers)
- 2 digital outputs (faults, unacknowledged faults)
- 2 analog inputs (2 sensor inputs for internal regulation and external setpoints)
- USB data interface

Software

- GBUS, Modbus RTU driver
- "Scan network" function for all systems
- Single control for controlling a unit
- Line control for controlling all units in a line
- Group control for controlling all units in a group
- Group formation for speed control of up to 10 freely definable groups
- Broadcast for controlling all connected units
- Control of 2 freely definable groups by means of an internal PI controller. Can be used for various control variables such as pressure, air velocity, volume flow, temperature, etc.
- Error output by means of a signal lamp and two separate, freely configurable (low/high active) control outputs for errors and "new unacknowledged" errors.
- Three operating levels (monitor / operator / administrator)
- Time control programmable scheduler for setpoint switching of individual FFUs, lines and all units

Nicotra Gebhardt Deutschland Nicotra Gebhardt GmbH Gebhardtstraße 19–25 74638 Waldenburg

Tel. +49 (0)7942 101 0 Fax +49 (0)7942 101 170 E-mail info@nicotra-gebhardt.com

NICOTRA Gebhardt